






Perforated Wall or Ceiling Panels: P0.5

- A wide range of surface finishes, colours and hole patterns available
- Low maintenance and easy to clean wooden panels.
- Engineered with high quality materials.

Surface Finish	Core	Soundtex Acoustic Felt on the back	Insulation
Natural Wood Veneers: Sapelli, Walnut, Mahogany, Cherry, Zebrano, Beech, Oak, Ash, Maple, Anigre. Decorative Laminate Range: Dark Oak, Dark Cherry, Aged Walnut, Walnut, Cherry, Light Oak, White Oak, Argent. Paint Finish: RAL colour range.	HDF/MDF Fire Rated ASTM E84 Class A Flame Spread Index 15 Smoke Developed Index 200	Yes	Metal/ Timber stud framing

Hole diameter (mm)	C-T-C Distance (mm)	Baseboard (mm) <small>(Holes at 16mm centres)</small>	Open Area %		Nominal Panel Weight (kg/m ²)
			Front	Back <small>(9mm holes at 16mm centres)</small>	
0.5	2.0	9	5.7	25	10.6

Panel Thickness (mm)	Panel Width (mm)	Panel Length (mm)	NRC E400 Mounting	Edge Profile
19mm+/- 0.5mm	600/1200 Custom sizes available	600/1200/2400	0.90 (with 50mm insul.)	Square edge



For more information visit www.sontext.com.au or contact Sontext or an Authorised Distributor



Head Office Australia / Vic State Office
 38C Merri Concourse,
 Campbellfield, VIC Australia 3061
 T: +61 (0)3 9432 2733
 E: sales@sontext.com.au

NSW State Office
 Suite 1a, Level 2, 802 Pacific Hwy
 Gordon, NSW, Australia 2702
 T: +61 (0)2 9844 5414