



SPECIFICATION SHEET

Perforated Wall or Ceiling Panels: S56

Surface Finish		Core	Soundtex Acoustic Felt on the back	Insulation	
Select from Natural Wood Veneers: Sapelli, Walnut, Mahogany, Cherry, Zebrano, Beech, Oak, Ash, Maple, Anigre Select from Decorative Laminate Range: Dark Oak, Dark Cherry, Aged Walnut, Walnut, Cherry, Light Oak, White Oak, Argent. Select Paint finish from RAL colour range		ECOBoard/ Standard E0 MDF/ Fire Rated MDF	Yes	Optional	
Nominal Panel Weight (kg/m ²)	C-T-C Distance Horizontal (mm)	C-T-C Distance Vertical (mm)			Open Area %
			Slot Width	Slot Length	
10.8	24	96	6	56	28.5
Panel Thickness (mm)	Panel Width (mm)	Panel Length (mm)	NRC E400 Mounting	Edge Profile	
16/18	600/1200 Custom sizes available	600/1200/2400	0.70	Square edge, Tongue and Groove Matching to face	

For further information, contact Sontext Pty Ltd or its Distributors:

Vic Office & Head Office Australia:

685 Burke Road, Camberwell, Victoria, Australia 3124

T: +61 (0)3 9811 4796 E: sales@sontext.com.au

NSW Office:

Suite 1a, Level 2, 802 Pacific Hwy, Gordon, NSW, Australia

2702 T: +61 (0)2 9844 5414

